


HOLES IN FLAT PADS FOR U-BOLTS CAN BE PRE-DRILLED OR LOCATED AND DRILLED AT THE TIME OF INSTALLATION.



ORDERING INFORMATION:

PART NUMBER: FP-1 - T - W - L **EXAMPLE:** FP-1 - 1/4 - 4 - 12

FP-1 FLAT PAD THICKNESS 1/4 4 **WIDTH** 12 **LENGTH**

APP'D BY: WC 12/04/18

SCALE: NTS

SHEET: 1 OF 1

NOTES:

- 1. RedLineIPS Composite Flat Pads are made from vinyl ester resin material, as manufactured by Cogbill Construction.
- 2. RedLineIPS Composite Flat Pads shall be installed as per the RedLineIPS installation procedures.
- 3. Produced in either 1/8" or 1/4" thicknesses. To be specified by customer.
- 4. Operating Temperature Range: -67°F (-55°C) to +400°F (204°C).
- 5. Epoxy fillet to be one continuous bead all around the wear pad for sealing it to the support steel.

GT HA 12/04/2018

6. Compressive load capacity rating of 113,000 lbs.

ISSUED FOR APPROVAL

7. Length and width is sized to fit support steel, minus 1/2" clearance in order to seal. To be specified by customer.

RE	/ DESCRIPTION	BY	СНК.	DATE	PIPING STANDARD DETAILS					
						REDLINEIPS BY COGBILL 2325 5 MAIN ST. VIDOR, TX 77662 409-768-1419 www.RedLineIPS.com Info@RedLineIPS.com				
					RedLineIPS NON-METALLIC					
					FLAT PADS					
0	ISSUED FOR CONSTRUCTION	GT	НА	12/18/2018	DRAWING NUMBER:	DRAWN BY: GT 12/04/18	CHK'D BY: HA 12/04/	18	REV: 0	
	ISSUED FOR ARRESTAL			10/04/0010	− FP-1	ADDID DV. M/C 12/04/19	CCALE NITC	CLIEFT	1.05.1	